

# Munken Polar

Extraordinary printing demands extraordinary design paper. The uncoated smooth surface of Munken Polar and its crispy white shade enhances images and has an exclusive, yet very natural feel. Munken Polar is developed for offset print and also suitable for various kinds of printing techniques; flexo, laser, xerography, digital printing, inkjet and for preprint applications. Available also is a cream shade, Munken Pure, and a natural white version, Munken Lynx. Munken Polar standard products are available as FSC™ and PEFC certified.

## MUNKEN POLAR - (DEC 09)

Grammage (g/m <sup>2</sup> )	80	90	100	120	130	150	170	200	240	300 <sup>b</sup>	400 <sup>b</sup>
Opacity (%)	89	91	93	95	96	97	98	99	99	100	100
Thickness (µm)	90	102	113	136	147	170	192	226	271	339	452
Bulk (thickness/grammage)											1.13
Whiteness (CIE)											145
Brightness (ISO 2470/D65 %)											109
Roughness (Bendtsen, ml/min)											150
Screen recommended 133-150 lpi											
Permanent document, acid free ISO 9706											
FSC, PEFC, ISO 14001, Paper Profile, EMAS											

Values are targets only and can be subject to changes over time without prior notice. You will find the latest valid technical specifications and information about our products at [www.arcticpaper.com](http://www.arcticpaper.com).

<sup>b</sup> Laminated paper



The mark of  
responsible forestry



Promoting sustainable forest  
management  
[www.pefc.org](http://www.pefc.org)

